


Réf : G6x36AT


**CABLE EN ACIER GALVANISÉ 6
TORONS DE 36 FILS (14+7/7+7+1).
Âme Textile.**



Item	Diamètre du câble (mm)	Rupture KN	
		1770	1960
01	8	37.40	—
02	10	58.4	—
03	12	84.1	—
04	14	114	—
05	16	150	166
06	18	189	210
07	20	234	259
08	22	283	313
09	24	336	373
10	26	395	437
11	28	458	507
12	30	526	582
13	32	598	662
14	34	675	748
15	36	757	838
16	38	843	934
17	40	935	1030
18	42	1030	1140

Réf : G6x36AM


**CABLE EN ACIER GALVANISÉ 6
TORONS DE 36 FILS (14+7/7+7+1).
Âme Métallique.**



Item	Diamètre du câble (mm)	Rupture KN	
		1770	1960
01	10	63	69.8
02	12	90.7	100
03	14	124	137
04	16	161	179
05	18	204	226
06	19	236.49	251
07	20	252	279
08	22	305	338
09	24	363	402
10	26	426	472
11	28	494	547
12	30	567	628
13	32	645	715
14	36	817	904
15	38	910	1010
16	40	1010	1120
17	42	1110	1230
18	44	1220	1350
19	78	3830	4250

Réf : 7X19AISI


**CABLE EN INOX
7 TORONS DE 19 FILS.**



Item	Diamètre du câble (mm)	Rupture KN	
		1560	1570
01	6	18.60	18.8
02	8		33.4
03	10	52.1	52.1
04	12	74.00	75.1
05	14	—	102
06	16	—	133

Réf : G8X25AM1960

**CABLE ACIER CLAIRE 8
TORONS DE 25 FILS.
Âme Métallique, 1960 N/mm²**



Item	Diamètre du câble (mm)	Rupture KN
01	8	43.40
02	10	67.8
03	12	97.5
04	15	152
05	16	173